



1 1 3 4 2

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-23A
	3
	160 L/min.
	350 bar
	blocked control port (dead headed)
	0,25 - 0,33 L/min.
-	5
	31,8 mm
	203 - 217 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0,60 kg
Seal kit - Cartridge	Buna: 990-023-007
Seal kit - Cartridge	Polyurethane: 990-023-002
Seal kit - Cartridge	Viton: 990-023-006

# OPTION SELECTION EXAMPLE: PVHDLANV

(L)	(A)	(N)	MATERIAL/COATING
L	A 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar)	N	Standard Material/Coating
C -	B 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar)	V	/AP
	D 25 - 800 psi (1,7 - 55 bar), 200 psi (14 bar)		
	E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)		
	W 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar)		

## TECHNICAL FEATURES

- 3 1:1 3000 psi 210 bar
- 1 2
- D, E, N Q 2000 psi (140 bar) A, B H 3000 psi (210 bar) C W
- /
- 4
- Sun /

## PERFORMANCE CURVES

