



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------|---------------------------|
| | T-21A |
| | 1 |
| | 60 L/min. |
| | 350 bar |
| 1 2 | 7 bar@60 L/min. |
| | 0,75 L/min. |
| | 0,3 bar |
| - | 5 |
| | 22,2 mm |
| | 41 - 47 Nm |
| | 4 mm |
| | 15 mm |
| | 9 - 10 Nm |
| | 0.19 kg. |
| Seal kit - Cartridge | Buna: 990-021-007 |
| Seal kit - Cartridge | Polyurethane: 990-021-002 |
| Seal kit - Cartridge | Viton: 990-021-006 |
| Seal kit - Cartridge | Buna: 990-021-007 |
| Seal kit - Cartridge | Polyurethane: 990-021-002 |
| Seal kit - Cartridge | Viton: 990-021-006 |

OPTION SELECTION EXAMPLE: QCDBLAN

| | (L) | (A) | (N) | MATERIAL/COATING |
|----------|----------|--|---------------------------|------------------|
| L | A | N | Standard Material/Coating | |
| C | V | /AP | | |
| - | - | /LH | | |
| | | A 1000 - 3000 psi (70 - 210 bar), 1000 psi (70 bar) B 500 - 1500 psi (35 - 105 bar), 500 psi (35 bar) C 2000 - 5000 psi (140 - 350 bar), 2000 psi (140 bar) D 250 - 800 psi (18 - 55 bar), 250 psi (18 bar) | | |

TECHNICAL FEATURES

-
-
-
-
-
-
- Sun / Sun
- Sun

PERFORMANCE CURVES

