



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|--------------------------------------------------------|---------------------------|
| Maximum Operating Pressure | 350 bar |
| Check Cracking Pressure | 0,3 bar |
| Pilot Flow Capacity | 0,75 L/min. |
| Pressure Drop, Port 1 to Port 2 | 7 bar@60 L/min. |
| Adjustment - No. of CW Turns from Min. to Max. setting | 5 |
| Locknut Hex Size | 15 mm |
| Locknut Torque | 9 - 10 Nm |
| Seal kit - Cartridge | Buna: 990-021-007 |
| Seal kit - Cartridge | Polyurethane: 990-021-002 |
| Seal kit - Cartridge | Viton: 990-021-006 |
| Seal kit - Cartridge | Buna: 990-021-007 |
| Seal kit - Cartridge | Polyurethane: 990-021-002 |
| Seal kit - Cartridge | Viton: 990-021-006 |

CONFIGURATION OPTIONS

Model Code Example: **QCDCLAN**

CONTROL

(L)

ADJUSTMENT RANGE

(A)

SEAL MATERIAL

(N)

L Standard Screw Adjustment

A 1000 - 3000 psi (70 - 210 bar), 1000 psi (70 bar)
Standard Setting

N Buna-N

V Viton