



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-21A
Series	1
Capacity	60 L/min.
Maximum Operating Pressure	350 bar
Check Cracking Pressure	0,3 bar
Pilot Flow Capacity	0,75 L/min.
Pressure Drop, Port 1 to Port 2	7 bar@60 L/min.
Adjustment - No. of CW Turns from Min. to Max. setting	5
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0.19 kg.
Seal kit - Cartridge	Buna: 990-021-007
Seal kit - Cartridge	Polyurethane: 990-021-002
Seal kit - Cartridge	Viton: 990-021-006

OPTION SELECTION EXAMPLE: QCDCLAN

CONTROL

(L) ADJUSTMENT RANGE

(A) SEAL MATERIAL

(N)

- L** Standard Screw Adjustment
- C** Tamper Resistant - Factory Set

A 1000 - 3000 psi (70 - 210 bar), 1000 psi (70 bar)
Standard Setting

- N** Buna-N
- V** Viton

PERFORMANCE CURVES

