



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-10A
	1
	1 L/min.
	350 bar
110 SUS (24 cSt)	0,3 cc/min.
	2 ms
-	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0,15 kg
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	EPDM: 990-010-014
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006

: • 0 1 0.75 in. (19 mm)

OPTION SELECTION EXAMPLE: RBACLANV

	(L)	(A)	(V)	MATERIAL/COATING
L		A 25 - 3000 psi (1,7 - 210 bar), 1000 psi (70 bar)	V	Standard Material/Coating
C	-		E EPDM	/AP
Y		B 25 - 1500 psi (1,7 - 105 bar), 1000 psi (70 bar)	N	/LH -
		D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar)		
		E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)		

TECHNICAL FEATURES

- 150
-
- 2 1:1
- EPDM
- W Y
- /AP
- Sun /

PERFORMANCE CURVES

