



This direct-acting, pilot relief cartridge incorporates back-to-back check valves. This allows it to remotely control 2 other pilot-operated valves or act as a thermal relief for both ends of an actuator. Because capacity is limited to pilot flow, this valve should be used with other valves with comparable pilot flows.

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Valve Leakage at 110 SUS (24 cSt)	5 drops/min.
Response Time - Typical	2 ms
Adjustment - No. of CW Turns from Min. to Max. setting	5
Locknut Hex Size	9/16 in.
Locknut Torque	80 - 90 lbf in.
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

**NOTES:** • For Series 1 cartridges configured with an O control (panel mount handknob), a .75 in. (19 mm) diameter hole is required in the panel.

**CONFIGURATION OPTIONS**

**Model Code Example: RBADLAN**

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>L</b> Standard Screw Adjustment		<b>A</b> 25 - 3000 psi (1,7 - 210 bar), 1000 psi (70 bar) Standard Setting		<b>N</b> Buna-N		Standard Material/Coating
<b>C</b> Tamper Resistant - Factory Set		<b>B</b> 25 - 1500 psi (1,7 - 105 bar), 1000 psi (70 bar) Standard Setting		<b>V</b> Viton		<b>/AP</b> Stainless Steel, Passivated
<b>K</b> Handknob		<b>D</b> 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting				<b>/LH</b> Mild Steel, Zinc-Nickel
		<b>E</b> 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting				