



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-11A
Series	1
Capacity	1 L/min.
Maximum Valve Leakage at 110 SUS (24 cSt)	0,3 cc/min.
Response Time - Typical	2 ms
Adjustment - No. of CW Turns from Min. to Max. setting	5
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

OPTION SELECTION EXAMPLE: RBADLAN

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
L Standard Screw Adjustment	A	25 - 3000 psi (1,7 - 210 bar), 1000 psi (70 bar) Standard Setting	N	Buna-N	Standard Material/Coating	
C Tamper Resistant - Factory Set	B	25 - 1500 psi (1,7 - 105 bar), 1000 psi (70 bar) Standard Setting	V	Viton	/AP	Stainless Steel, Passivated
	C	25 - 6000 psi (1,7 - 420 bar), 1000 psi (70 bar) Standard Setting			/LH	Mild Steel, Zinc-Nickel
	D	25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting				
	E	25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting				
	W	25 - 4500 psi (1,7 - 315 bar), 1000 psi (70 bar) Standard Setting				

PERFORMANCE CURVES

