



2

1

1 2

T-8A

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-8A
	P
	10 L/min.
	350 bar
110 SUS (24 cSt)	1 cc/min.
	30 cc/min.
	2 ms
	22,2 mm
	27 - 33 Nm
	4 mm
	15 mm
	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-608-007
Seal kit - Cartridge	EPDM: 990-608-014
Seal kit - Cartridge	Polyurethane: 990-008-002
Seal kit - Cartridge	Viton: 990-608-006
Seal kit - Cartridge	Buna: 990-608-007
Seal kit - Cartridge	EPDM: 990-608-014
Seal kit - Cartridge	Polyurethane: 990-008-002
Seal kit - Cartridge	Viton: 990-608-006

: • 0 1 0.75 in. (19 mm)

OPTION SELECTION EXAMPLE: RBAELAN

	(L)	(A)	(N)	MATERIAL/COATING
L O	A 25 - 3000 psi (1,7 - 210 bar), 1000 psi (70 bar) B 25 - 1500 psi (1,7 - 105 bar), 1000 psi (70 bar)	N E EPDM V	Standard Material/Coating /AP /LH -	

TECHNICAL FEATURES

- Sun T-8A 2 Sun 2 2
- -8 T-8A
- 1 2 5000 psi (350 bar)
-
- 2 1
- EPDM
- Sun /

PERFORMANCE CURVES

