



2 1 1 2 T-8A

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	350 bar
110 SUS (24 cSt)	1 cc/min.
	30 cc/min.
	2 ms
	15 mm
	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-608-007
Seal kit - Cartridge	EPDM: 990-608-014
Seal kit - Cartridge	Polyurethane: 990-008-002
Seal kit - Cartridge	Viton: 990-608-006

: • O 1 0.75 in. (19 mm)

**CONFIGURATION OPTIONS**

**Model Code Example: RBAELANV**

(L)	(A)	(V)	MATERIAL/COATING
<b>L</b>	<b>A</b> 25 - 3000 psi (1,7 - 210 bar), 1000 psi (70 bar)	<b>V</b>	Standard Material/Coating
<b>C</b> -	<b>B</b> 25 - 1500 psi (1,7 - 105 bar), 1000 psi (70 bar)	<b>E</b> EPDM	/AP
<b>Y</b>	<b>D</b> 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar)	<b>N</b>	/LH -
	<b>E</b> 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)		