



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Seal kit - Cartridge	Buna: 990-208-007
Seal kit - Cartridge	Viton: 990-208-006

**CONFIGURATION OPTIONS**

**Model Code Example: RBANXAN**

CONTROL	(X)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	BOBINA
<b>X</b> No Manual Override		<b>A</b> 3000 - 1500 psi (105 - 210 bar)		<b>N</b> Buna-N		No coil
		<b>B</b> 1500 - 800 psi (55 - 105 bar)		<b>V</b> Viton		<b>224NX01</b> DIN 43650-Form A, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
		<b>D</b> 800 - 300 psi (20 - 55 bar)				<b>224NX02</b> DIN 43650-Form A, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver
		<b>W</b> 5000 - 3000 psi (210 - 350 bar)				<b>912NX01</b> Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
						<b>912NX02</b> Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver
						<b>924NX01</b> Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
						<b>924NX02</b> Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver