



2

**PROPORTIONAL PERFORMANCE DATA**

	<4%
	<8%
	<2%
( )	<2%
	140 Hz
Seal kit - Cartridge	Buna: 990-208-007
Seal kit - Cartridge	Viton: 990-208-006

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-8A
	P
	1 L/min.
	350 bar
	25 cc/min.
	>85% of setting
	19 mm
	22,2 mm
	27 - 33 Nm
	0,45 kg
Seal and nut kit - Coil	Viton: 990-770-006
Seal kit - Cartridge	Buna: 990-208-007
Seal kit - Cartridge	Viton: 990-208-006

# OPTION SELECTION EXAMPLE: RBANXAN

	(X)	(A)	(N)
<b>X</b>	<b>A</b> 3000 - 1500 psi (105 - 210 bar)	<b>N</b>	
	<b>B</b> 1500 - 800 psi (55 - 105 bar)	<b>V</b>	
	<b>D</b> 800 - 300 psi (20 - 55 bar)		
	<b>W</b> 5000 - 3000 psi (210 - 350 bar)		
			<b>224NX01</b> DIN 43650 A 24 VDC (TVS) XMD-01 <b>224NX02</b> DIN 43650 A 24 VDC (TVS) XMD-02 <b>912NX01</b> Deutsch DT04-2P 12 VDC (TVS) XMD-01 <b>912NX02</b> Deutsch DT04-2P 12 VDC (TVS) XMD-02 <b>924NX01</b> Deutsch DT04-2P 24 VDC (TVS) XMD-01 <b>924NX02</b> Deutsch DT04-2P 24 VDC (TVS) XMD-02

## TECHNICAL FEATURES

- 
- 
- Sun T-8A 2 Sun 2
- 
- -8 T-8A
- 
- 85%
- Sun
- 100-250 HZ
- Sun /

## PERFORMANCE CURVES



