



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Seal kit - Cartridge	Buna: 990-208-007
Seal kit - Cartridge	EPDM: 990-008-014
Seal kit - Cartridge	Viton: 990-208-006

CONFIGURATION OPTIONS

Model Code Example: RBAPXAN

CONTROL	(X)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	BOBINA
X No Manual Override		A 300 - 3000 psi (20 - 210 bar)		N Buna-N		No coil
E Twist (Extended) Manual Override		B 150 - 1500 psi (10,5 - 105 bar)		E EPDM		212 DIN 43650-Form A, 12 VDC
L Manual Override - Adjustable		D 50 - 750 psi (3,5 - 50 bar)		V Viton		224 DIN 43650-Form A, 24 VDC
T Tuning Adjustment		W 500 - 5000 psi (35 - 350 bar)				224NX01 DIN 43650-Form A, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
						224NX02 DIN 43650-Form A, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver
						912 Deutsch DT04-2P, 12 VDC
						912NX01 Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
						912NX02 Deutsch DT04-2P, 12 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver
						924 Deutsch DT04-2P, 24 VDC
						924NX01 Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-01 driver
						924NX02 Deutsch DT04-2P, 24 VDC, no transient voltage suppression (TVS) diodes, with XMD-02 driver