



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-10A
Series	1
Capacity	95 L/min.
Maximum Operating Pressure	350 bar
Factory Pressure Settings Established at	15 L/min.
Maximum Valve Leakage at Reseat	0,7 cc/min.
Response Time - Typical	2 ms
Reseat	>85% of setting
Hysteresis	≤ 3 %
Adjustment - No. of CW Turns from Min. to Max. setting	5
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Model Weight	0.17 kg.
Seal kit - Cartridge	Buna: 990-310-007
Seal kit - Cartridge	Viton: 990-310-006
U.S. Patent #	11,384,857

OPTION SELECTION EXAMPLE: RBDALAN

CONTROL

- L** Standard Screw Adjustment
- C** Tamper Resistant - Factory Set

(L) ADJUSTMENT RANGE

- A** 1200 - 3000 psi (85-210 bar), 1500 psi (105 bar) Standard Setting
- W** 3000 - 5000 psi (210 - 350 bar), 4000 psi (280 bar) Standard Setting

(A) SEAL MATERIAL

- N** Buna-N
- V** Viton

(N)

PERFORMANCE CURVES

