



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|--|--------------------|
| cavidad | T-10A |
| Series | 1 |
| Capacity | 95 L/min. |
| Maximum Operating Pressure | 350 bar |
| Factory Pressure Settings Established at | 15 L/min. |
| Maximum Valve Leakage at Reseat | 0,7 cc/min. |
| Response Time - Typical | 2 ms |
| Reseat | >90% of setting |
| Valve Hex Size | 22,2 mm |
| Valve Installation Torque | 41 - 47 Nm |
| Model Weight | 0.15 kg. |
| Seal kit - Cartridge | Buna: 990-310-007 |
| Seal kit - Cartridge | Viton: 990-310-006 |

OPTION SELECTION EXAMPLE: RDDA3AN

ADJUSTMENT RANGE

- A 500 - 3000 psi (35 - 210 bar)
- C 1000 - 6000 psi (70 - 420 bar)
- D 200 - 800 psi (14 - 55 bar)

(A) SEAL MATERIAL

- N Buna-N
- V Viton

(N) MATERIAL/COATING

- Standard Material/Coating
- /LH Mild Steel, Zinc-Nickel

PERFORMANCE CURVES

