



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-10A
Series	1
Capacity	95 L/min.
Maximum Operating Pressure	350 bar
Factory Pressure Settings Established at	15 L/min.
Maximum Valve Leakage at Reseat	0,7 cc/min.
Response Time - Typical	2 ms
Reseat	>90% of setting
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Model Weight	0.15 kg.
Seal kit - Cartridge	Buna: 990-310-007
Seal kit - Cartridge	Viton: 990-310-006
Seal kit - Cartridge	Buna: 990-310-007
Seal kit - Cartridge	Viton: 990-310-006

OPTION SELECTION EXAMPLE: RDDA3AN

ADJUSTMENT RANGE

- A 500 - 3000 psi (35 - 210 bar)
- C 1000 - 6000 psi (70 - 420 bar)
- D 200 - 800 psi (14 - 55 bar)

(A) SEAL MATERIAL

- N Buna-N
- V Viton

(N) MATERIAL/COATING

- Standard Material/Coating
- /LH Mild Steel, Zinc-Nickel

PERFORMANCE CURVES

