



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------|---------------------------|
| | T-3A |
| | 2 |
| | 200 L/min. |
| | 350 bar |
| | 0,7 cc/min. |
| | 15 L/min. |
| | 2 ms |
| | >90% of setting |
| | 28,6 mm |
| | 61 - 68 Nm |
| | 0.28 kg. |
| Seal kit - Cartridge | Buna: 990-303-007 |
| Seal kit - Cartridge | EPDM: 990-303-014 |
| Seal kit - Cartridge | Polyurethane: 990-303-002 |
| Seal kit - Cartridge | Viton: 990-303-006 |
| Seal kit - Cartridge | Buna: 990-303-007 |
| Seal kit - Cartridge | EPDM: 990-303-014 |
| Seal kit - Cartridge | Polyurethane: 990-303-002 |
| Seal kit - Cartridge | Viton: 990-303-006 |

OPTION SELECTION EXAMPLE: RDFA3AN

(A)

(N)

| | | | |
|---|--------------------------------|---|---|
| A | 500 - 3000 psi (35 - 210 bar) | N | V |
| C | 1000 - 6000 psi (70 - 420 bar) | | |
| D | 200 - 800 psi (14 - 55 bar) | | |

TECHNICAL FEATURES

-
- EPDM
- 2
- 2
-
-
-
- 2 1:1
- Sun /
- : A - 2000 psi (138 bar), B - 1000 psi (69 bar), C - 4000 psi (276 bar), D - 800 psi (55 bar), E - 400 psi (28 bar), S - 13000 psi (207 bar)
- 90%

PERFORMANCE CURVES

