



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Seal kit - Cartridge	Buna: 990-162-007
Seal kit - Cartridge	EPDM: 990-162-014
Seal kit - Cartridge	Polyurethane: 990-162-002
Seal kit - Cartridge	Viton: 990-162-006

CONFIGURATION OPTIONS

Model Code Example: RPCCLAN

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
L Standard Screw Adjustment		A 75 - 3000 psi (5 - 210 bar), 1000 psi (70 bar) Standard Setting		N Buna-N		Standard Material/Coating
C Tamper Resistant - Factory Set		B 75 - 1500 psi (5 - 105 bar), 1000 psi (70 bar) Standard Setting		E EPDM		/AP Stainless Steel, Passivated
F Hex Head Screw with Locknut		C 75 - 6000 psi (5 - 420 bar), 1000 psi (70 bar) Standard Setting		V Viton		/LH Mild Steel, Zinc-Nickel
		N 75 - 800 psi (5 - 55 bar), 400 psi (28 bar) Standard Setting				
		Q 75 - 400 psi (5 - 28 bar), 200 psi (14 bar) Standard Setting				
		W 75 - 4500 psi (5 - 315 bar), 1000 psi (70 bar) Standard Setting				