



CONFIGURATION

| | |
|---------------------------|--|
| F Control | Hex Head Screw with Locknut |
| A Adjustment Range | 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting |
| N Seal Material | Buna-N |
| Material/Coating | |

TECHNICAL DATA

| | |
|----------------------|---------------------------|
| Seal kit - Cartridge | Buna: 990-010-007 |
| Seal kit - Cartridge | EPDM: 990-010-014 |
| Seal kit - Cartridge | Polyurethane: 990-010-002 |
| Seal kit - Cartridge | Viton: 990-010-006 |

CONFIGURATION OPTIONS

Model Code Example: RPECFAN

| CONTROL | (F) | ADJUSTMENT RANGE | (A) | SEAL MATERIAL | (N) | MATERIAL/COATING | (/LH) |
|---|-----|--|-----|-----------------|-----|--|-------|
| F Hex Head Screw with Locknut | | A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting | | N Buna-N | | /LH Mild Steel, Zinc-Nickel | |
| C Tamper Resistant - Factory Set | | B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting | | E EPDM | | /AP Stainless Steel, Passivated | |
| K manilla | | C 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) Standard Setting | | V Viton | | Standard Material/Coating | |
| L Standard Screw Adjustment | | D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting | | | | | |
| O Handknob with Panel Mount | | E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting | | | | | |
| W Hex Wrench Adjustment | | W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting | | | | | |
| Y manilla de tres agarres | | | | | | | |