



CONFIGURATION

F
A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)

1

NOTE: DATA MAY VARY FROM LISTED VALUES. SEE CONFIGURATION SECTION.

TECHNICAL DATA

	T-10A
	1
	95 L/min.
	350 bar
110 SUS (24 cSt)	30 cc/min. @70 bar
	15 L/min.
	10 ms
-	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.13 kg.
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	EPDM: 990-010-014
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	EPDM: 990-010-014
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006

: • 0 1 0.75 in. (19 mm)

OPTION SELECTION EXAMPLE: RPECFAN

(F)

(A)

F	A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)
C -	B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)
K	C 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar)
L	N 60 - 800 psi (4 - 55 bar), 400 psi (28 bar)
O	Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)
W	W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)
Y	

TECHNICAL FEATURES

- 2
- 2
- 150
-
- 2 1:1
- EPDM
- W Y
- /AP
- Sun /

PERFORMANCE CURVES

