



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-10A
Series	1
Capacity	95 L/min.
Maximum Operating Pressure	350 bar
Control Pilot Flow	0,11 - 0,16 L/min.
Main stage leakage at 110 SUS (24 cSt)	30 cc/min.@70 bar
Pilot Control Cavity	T-8A
Pilot Control Valve Hex Size	22,2 mm
Pilot Control Valve Installation Torque	27 - 33 Nm
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Model Weight	0.09 kg.
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	EPDM: 990-010-014
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006

OPTION SELECTION EXAMPLE: RPEC8WN

ADJUSTMENT RANGE

(W) SEAL MATERIAL

(N)

W 100 - 5000 psi (7 - 350 bar)	N Buna-N
D 25 - 3000 psi (1,7 - 210 bar)	E EPDM
	V Viton

PERFORMANCE CURVES

