



T-8A

1

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------|---------------------------|
| | T-10A |
| | 1 |
| | 95 L/min. |
| | 350 bar |
| | T-8A |
| | 22,2 mm |
| | 27 - 33 Nm |
| 110 SUS 24 cSt | 30 cc/min. @70 bar |
| | 0,11 - 0,16 L/min. |
| | 22,2 mm |
| | 41 - 47 Nm |
| | 0.09 kg. |
| Seal kit - Cartridge | Buna: 990-010-007 |
| Seal kit - Cartridge | EPDM: 990-010-014 |
| Seal kit - Cartridge | Polyurethane: 990-010-002 |
| Seal kit - Cartridge | Viton: 990-010-006 |
| Seal kit - Cartridge | Buna: 990-010-007 |
| Seal kit - Cartridge | EPDM: 990-010-014 |
| Seal kit - Cartridge | Polyurethane: 990-010-002 |
| Seal kit - Cartridge | Viton: 990-010-006 |

OPTION SELECTION EXAMPLE: RPEC8WN

(W)

(N)

W 100 - 5000 psi (7 - 350 bar)

N

D 25 - 3000 psi (1,7 - 210 bar)

E EPDM

V

TECHNICAL FEATURES

- 2
- 2
- 150
-
- 2 1:1
- -8 T-8A
- -8 T-8A
- EPDM
- Sun /

T-8A

PERFORMANCE CURVES

