



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|                      |                           |
|----------------------|---------------------------|
| Seal kit - Cartridge | Buna: 990-010-007         |
| Seal kit - Cartridge | Polyurethane: 990-010-002 |
| Seal kit - Cartridge | Viton: 990-010-006        |

**CONFIGURATION OPTIONS**

**Model Code Example: RPEELAN**

| CONTROL (L)                             | ADJUSTMENT RANGE (A)   | SEAL MATERIAL (N) | MATERIAL/COATING                |
|---|--|-------------------|---------------------------------|
| <b>L</b> Standard Screw Adjustment      | <b>A</b> 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting    | <b>N</b> Buna-N   | Standard Material/Coating       |
| <b>C</b> Tamper Resistant - Factory Set | <b>B</b> 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting   | <b>V</b> Viton    | /AP Stainless Steel, Passivated |
| <b>F</b> Hex Head Screw with Locknut    | <b>C</b> 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) Standard Setting |                   | /LH Mild Steel, Zinc-Nickel     |
| <b>Y</b> manilla de tres agarres        | <b>D</b> 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting      |                   |                                 |
|   | <b>E</b> 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting      |                   |                                 |
|   | <b>N</b> 60 - 800 psi (4 - 55 bar), 400 psi (28 bar) Standard Setting        |                   |                                 |
|   | <b>Q</b> 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting        |                   |                                 |
|   | <b>W</b> 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting |                   |                                 |