



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-10A
Series	1
Capacity	95 L/min.
Maximum Operating Pressure	350 bar
Control Pilot Flow	0,16 - 0,41 L/min.
Factory Pressure Settings Established at	15 L/min.
Main stage leakage at reseal	0,7 cc/min.
Pilot Control Cavity	T-8A
Pilot Control Valve Hex Size	22,2 mm
Pilot Control Valve Installation Torque	27 - 33 Nm
Response Time - Typical	7 ms
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Model Weight	0.09 kg.
Seal kit - Cartridge	Buna: 990-310-007
Seal kit - Cartridge	EPDM: 990-310-014
Seal kit - Cartridge	Viton: 990-310-006

OPTION SELECTION EXAMPLE: RPES8WN

ADJUSTMENT RANGE
(W)
SEAL MATERIAL
(N)
MATERIAL/COATING
W 1000 - 5000 psi (70 - 350 bar)

N Buna-N

Standard Material/Coating

D 50 - 1500 psi (3,5 - 105 bar)

E EPDM

/LH Mild Steel, Zinc-Nickel

V Viton

PERFORMANCE CURVES

