



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	EPDM: 990-203-014
Seal kit - Cartridge	Polyurethane: 990-003-002
Seal kit - Cartridge	Viton: 990-203-006

CONFIGURATION OPTIONS

Model Code Example: RPGCLAN

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
L Standard Screw Adjustment		A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting		N Buna-N		Standard Material/Coating
C Tamper Resistant - Factory Set		B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting		E EPDM		/AP Stainless Steel, Passivated
F Hex Head Screw with Locknut		C 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) Standard Setting		V Viton		/LH Mild Steel, Zinc-Nickel
W Hex Wrench Adjustment		D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting				
Y manilla de tres agarres		E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting				
		N 60 - 800 psi (4 - 55 bar), 400 psi (28 bar) Standard Setting				
		Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting				
		W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting				