



### CONFIGURATION

<b>L</b> Control	Standard Screw Adjustment
<b>N</b> Adjustment Range	60 - 800 psi (4 - 55 bar), 400 psi (28 bar) Standard Setting
<b>N</b> Seal Material	Buna-N
Material/Coating	

### TECHNICAL DATA

Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	EPDM: 990-203-014
Seal kit - Cartridge	Polyurethane: 990-003-002
Seal kit - Cartridge	Viton: 990-203-006

### CONFIGURATION OPTIONS

#### Model Code Example: RPGCLNN

CONTROL (L)	ADJUSTMENT RANGE (N)	SEAL MATERIAL (N)	MATERIAL/COATING (/LH)
<b>L</b> Standard Screw Adjustment	<b>N</b> 60 - 800 psi (4 - 55 bar), 400 psi (28 bar) Standard Setting	<b>N</b> Buna-N	<b>/LH</b> Mild Steel, Zinc-Nickel
<b>C</b> Tamper Resistant - Factory Set	<b>A</b> 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting	<b>E</b> EPDM	<b>/AP</b> Stainless Steel, Passivated
<b>Y</b> manilla de tres agarres	<b>B</b> 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting	<b>V</b> Viton	Standard Material/Coating
	<b>C</b> 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) Standard Setting		
	<b>D</b> 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting		
	<b>E</b> 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting		
	<b>J</b> 25 - 1500 psi (1,7 - 105 bar), 1000 psi (70 bar) Standard Setting		
	<b>K</b> 75 - 1500 psi (5 - 105 bar), 1000 psi (70 bar) Standard Setting		
	<b>Q</b> 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting		
	<b>S</b> 25 - 200 psi (1,7 - 14 bar), 100 psi (7 bar) Standard Setting		
	<b>W</b> 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting		