



CONFIGURATION

L Control	Standard Screw Adjustment
N Adjustment Range	60 - 800 psi (4 - 55 bar), 400 psi (28 bar) Standard Setting
N Seal Material	Buna-N
Material/Coating	

TECHNICAL DATA

Maximum Operating Pressure	350 bar
Factory Pressure Settings Established at	15 L/min.
Maximum Valve Leakage at 110 SUS (24 cSt)	50 cc/min.@70 bar
Response Time - Typical	10 ms
Adjustment - No. of CW Turns from Min. to Max. setting	5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	EPDM: 990-203-014
Seal kit - Cartridge	Polyurethane: 990-003-002
Seal kit - Cartridge	Viton: 990-203-006
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	EPDM: 990-203-014
Seal kit - Cartridge	Polyurethane: 990-003-002
Seal kit - Cartridge	Viton: 990-203-006

CONFIGURATION OPTIONS

Model Code Example: RPGCLNN

CONTROL	(L)	ADJUSTMENT RANGE	(N)	SEAL MATERIAL	(N)	MATERIAL/COATING	(/LH)
L Standard Screw Adjustment		N 60 - 800 psi (4 - 55 bar), 400 psi (28 bar) Standard Setting		N Buna-N		/LH Mild Steel, Zinc-Nickel	
C Tamper Resistant - Factory Set		A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting		E EPDM		/AP Stainless Steel, Passivated	
J Capped Screw Adjustment		B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting		V Viton		Standard Material/Coating	
K manilla		D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting					
		E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting					
		J 25 - 1500 psi (1,7 - 105 bar), 1000 psi (70 bar) Standard Setting					
		K 75 - 1500 psi (5 - 105 bar), 1000 psi (70 bar) Standard Setting					
		S 25 - 200 psi (1,7 - 14 bar), 100 psi (7 bar) Standard Setting					
		W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting					