



CONFIGURATION

L	
N	60 - 800 psi (4 - 55 bar), 400 psi (28 bar)
N	
	Material/Coating

1

TECHNICAL DATA

	350 bar
110 SUS (24 cSt)	50 cc/min.@70 bar
	15 L/min.
	10 ms
-	5
	15 mm
	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	EPDM: 990-203-014
Seal kit - Cartridge	Polyurethane: 990-003-002
Seal kit - Cartridge	Viton: 990-203-006
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	EPDM: 990-203-014
Seal kit - Cartridge	Polyurethane: 990-003-002
Seal kit - Cartridge	Viton: 990-203-006

: • O 1 0.75 in. (19 mm)

CONFIGURATION OPTIONS

Model Code Example: RPGCLNN

	(L)	(N)	(N)	MATERIAL/COATING	(/LH)
L		N 60 - 800 psi (4 - 55 bar), 400 psi (28 bar)	N	/LH -	
C	-		E EPDM	/AP	
J		A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	V		Standard Material/Coating
K		B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)			
O		C 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar)			
W		D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar)			
Y		E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)			
		Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)			
		W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)			