



1

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-3A
	2
	200 L/min.
	350 bar
110 SUS (24 cSt)	50 cc/min. @70 bar
	15 L/min.
	2 ms
-	5
	28,6 mm
	61 - 68 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.26 kg.
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	EPDM: 990-203-014
Seal kit - Cartridge	Polyurethane: 990-003-002
Seal kit - Cartridge	Viton: 990-203-006
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	EPDM: 990-203-014
Seal kit - Cartridge	Polyurethane: 990-003-002
Seal kit - Cartridge	Viton: 990-203-006

: • 0 1 0.75 in. (19 mm)

OPTION SELECTION EXAMPLE: RPGELAN

	(L)	(A)	(N)	MATERIAL/COATING
L	A	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	N	Standard Material/Coating
J			E EPDM	/AP
O		Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)	V	/LH

TECHNICAL FEATURES

- 2
- 2
- 150
-
- 2 1:1
- EPDM
- Sun /

PERFORMANCE CURVES

