



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Factory Pressure Settings Established at	15 L/min.
Maximum Valve Leakage at Reseat	0,7 cc/min.
Response Time - Typical	7 ms
Adjustment - No. of CW Turns from Min. to Max. setting	5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-303-007
Seal kit - Cartridge	EPDM: 990-303-014
Seal kit - Cartridge	Polyurethane: 990-303-002
Seal kit - Cartridge	Viton: 990-303-006
Seal kit - Cartridge	Buna: 990-303-007
Seal kit - Cartridge	EPDM: 990-303-014
Seal kit - Cartridge	Polyurethane: 990-303-002
Seal kit - Cartridge	Viton: 990-303-006

**CONFIGURATION OPTIONS**

**Model Code Example: RPGSLAN**

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
L Standard Screw Adjustment		A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting		N Buna-N		Standard Material/Coating
C Tamper Resistant - Factory Set		B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting		E EPDM		/AP Stainless Steel, Passivated
K manilla		W 100 - 4500 psi (7 - 315 bar), 1000 psi (70 bar) Standard Setting		V Viton		/LH Mild Steel, Zinc-Nickel