



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-3A
Series	2
Capacity	200 L/min.
Maximum Operating Pressure	350 bar
Factory Pressure Settings Established at	15 L/min.
Maximum Valve Leakage at Reseat	0,7 cc/min.
Response Time - Typical	7 ms
Adjustment - No. of CW Turns from Min. to Max. setting	5
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0.26 kg.
Seal kit - Cartridge	Buna: 990-303-007
Seal kit - Cartridge	EPDM: 990-303-014
Seal kit - Cartridge	Polyurethane: 990-303-002
Seal kit - Cartridge	Viton: 990-303-006

## OPTION SELECTION EXAMPLE: RPGSLAN

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>L</b>	Standard Screw Adjustment	<b>A</b>	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting	<b>N</b>	Buna-N	Standard Material/Coating
<b>C</b>	Tamper Resistant - Factory Set	<b>B</b>	50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting	<b>E</b>	EPDM	/AP Stainless Steel, Passivated
<b>Y</b>	manilla de tres agarres	<b>C</b>	150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) Standard Setting	<b>V</b>	Viton	/LH Mild Steel, Zinc-Nickel
		<b>N</b>	60 - 800 psi (4 - 55 bar), 400 psi (28 bar) Standard Setting			
		<b>Q</b>	60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting			
		<b>W</b>	100 - 4500 psi (7 - 315 bar), 1000 psi (70 bar) Standard Setting			

### PERFORMANCE CURVES

