



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-3A
Series	2
Capacity	200 L/min.
Maximum Operating Pressure	350 bar
Control Pilot Flow	0,16 - 0,25 L/min.
Main stage leakage at reseal	0,7 cc/min.
Pilot Control Cavity	T-8A
Pilot Control Valve Hex Size	22,2 mm
Pilot Control Valve Installation Torque	27 - 33 Nm
Response Time - Typical	2 ms
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Model Weight	0.18 kg.
Seal kit - Cartridge	Buna: 990-303-007
Seal kit - Cartridge	EPDM: 990-303-014
Seal kit - Cartridge	Polyurethane: 990-303-002
Seal kit - Cartridge	Viton: 990-303-006

# OPTION SELECTION EXAMPLE: RPGS8WN

## ADJUSTMENT RANGE

(W)

## SEAL MATERIAL

(N)

**W** 100 - 5000 psi (7 - 350 bar)

**N** Buna-N

**B** 50 - 1500 psi (3,5 - 105 bar)

**E** EPDM

**V** Viton

## PERFORMANCE CURVES

