



### CONFIGURATION

<b>L</b> Control	Standard Screw Adjustment
<b>N</b> Adjustment Range	60 - 800 psi (4 - 55 bar), 400 psi (28 bar) Standard Setting
<b>N</b> Seal Material	Buna-N
Material/Coating	

Pilot-operated, balanced-piston relief cartridges are normally closed pressure regulating valves. When the pressure at the inlet (port 1) reaches the valve setting, the valve starts to open to tank (port 2), throttling flow to regulate the pressure. These valves are accurate, have low pressure rise vs. flow, they are smooth and quiet, and are moderately fast.

they are smooth and quiet, and are moderately fast.

### TECHNICAL DATA

Maximum Operating Pressure	5000 psi
Factory Pressure Settings Established at	4 gpm
Maximum Valve Leakage at 110 SUS (24 cSt)	4 in <sup>3</sup> /min.@1000 psi
Response Time - Typical	10 ms
Adjustment - No. of CW Turns from Min. to Max. setting	5
Locknut Hex Size	9/16 in.
Locknut Torque	80 - 90 lbf in.
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	EPDM: 990-016-014
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006

### CONFIGURATION OPTIONS

#### Model Code Example: RPICLNN

CONTROL	(L)	ADJUSTMENT RANGE	(N)	SEAL MATERIAL	(N)	MATERIAL/COATING	((LH)
<b>L</b> Standard Screw Adjustment		<b>N</b> 60 - 800 psi (4 - 55 bar), 400 psi (28 bar) Standard Setting		<b>N</b> Buna-N		<b>/LH</b> Mild Steel, Zinc-Nickel	
<b>C</b> Tamper Resistant - Factory Set		<b>A</b> 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting		<b>E</b> EPDM		<b>/AP</b> Stainless Steel, Passivated	
<b>W</b> Hex Wrench Adjustment		<b>B</b> 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting		<b>V</b> Viton		Standard Material/Coating	
<b>Y</b> Tri-Grip Handknob		<b>C</b> 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) Standard Setting					
		<b>D</b> 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting					
		<b>E</b> 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting					
		<b>Q</b> 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting					
		<b>W</b> 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting					