



CONFIGURATION

L	Control	Standard Screw Adjustment
N	Adjustment Range	60 - 800 psi (4 - 55 bar), 400 psi (28 bar) Standard Setting
N	Seal Material	Buna-N
	Material/Coating	

TECHNICAL DATA

Maximum Operating Pressure	350 bar
Factory Pressure Settings Established at	15 L/min.
Maximum Valve Leakage at 110 SUS (24 cSt)	65 cc/min. @70 bar
Response Time - Typical	10 ms
Adjustment - No. of CW Turns from Min. to Max. setting	5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	EPDM: 990-016-014
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	EPDM: 990-016-014
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006

CONFIGURATION OPTIONS

Model Code Example: RPICLNN

CONTROL	(L)	ADJUSTMENT RANGE	(N)	SEAL MATERIAL	(N)	MATERIAL/COATING	(/LH)
L	Standard Screw Adjustment	N	60 - 800 psi (4 - 55 bar), 400 psi (28 bar) Standard Setting	N	Buna-N	/LH	Mild Steel, Zinc-Nickel
C	Tamper Resistant - Factory Set	A	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting	E	EPDM	/AP	Stainless Steel, Passivated
K	manilla	B	50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting	V	Viton		Standard Material/Coating
		D	25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting				
		E	25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting				
		W	150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting				