



CONFIGURATION

L	
N	60 - 800 psi (4 - 55 bar), 400 psi (28 bar)
N	
	Material/Coating

1

NOTE: DATA MAY VARY FROM TECHNICAL DATA SEE CONFIGURATION SECTION.

	T-16A
	3
	380 L/min.
	350 bar
110 SUS (24 cSt)	65 cc/min.@70 bar
	15 L/min.
	10 ms
-	5
	31,8 mm
	203 - 217 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.54 kg.
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	EPDM: 990-016-014
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	EPDM: 990-016-014
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006

OPTION SELECTION EXAMPLE: RPICLNN

	(L)	(N)	(N)	MATERIAL/COATING	(/LH)
L	-	N 60 - 800 psi (4 - 55 bar), 400 psi (28 bar)	N	/LH	-
C	-		E EPDM	/AP	
W		A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	V		Standard Material/Coating
Y		B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)			
		C 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar)			
		D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar)			
		E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)			
		Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)			
		W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)			

TECHNICAL FEATURES

- 2
- 2
- 150
-
- 2 1:1
- EPDM
- W Y
- /AP
- Sun /

PERFORMANCE CURVES



