



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-16A
	3
	380 L/min.
	350 bar
	0,7 cc/min.
	15 L/min.
	7 ms
	5
	31,8 mm
	203 - 217 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.55 kg.
Seal kit - Cartridge	Buna: 990-316-007
Seal kit - Cartridge	EPDM: 990-316-014
Seal kit - Cartridge	Viton: 990-316-006
Seal kit - Cartridge	Buna: 990-316-007
Seal kit - Cartridge	EPDM: 990-316-014
Seal kit - Cartridge	Viton: 990-316-006

OPTION SELECTION EXAMPLE: RPISLAN

(L)	(A)	(N)	MATERIAL/COATING
L	A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)	N E EPDM V	Standard Material/Coating /AP /LH -

TECHNICAL FEATURES

-
- 2
-
- 150
-
- 2 1:1
- EPDM
- W Y
- /AP
- Sun /

PERFORMANCE CURVES

