



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|-----------------------------|---------------------------|
| cavidad | T-16A |
| Series | 3 |
| Capacity | 380 L/min. |
| Maximum Operating Pressure | 350 bar |
| Control Pilot Flow | 0,25 - 0,33 L/min. |
| Main stage leakage at reset | 0,7 cc/min. |
| Pilot Control Cavity | T-8A |
| Response Time - Typical | 2 ms |
| Valve Hex Size | 31,8 mm |
| Valve Installation Torque | 203 - 217 Nm |
| Model Weight | 0,55 kg |
| Seal kit - Cartridge | Buna: 990-316-007 |
| Seal kit - Cartridge | EPDM: 990-316-014 |
| Seal kit - Cartridge | Polyurethane: 990-016-002 |
| Seal kit - Cartridge | Viton: 990-316-006 |
| Seal kit - Cartridge | Buna: 990-316-007 |
| Seal kit - Cartridge | EPDM: 990-316-014 |
| Seal kit - Cartridge | Polyurethane: 990-016-002 |
| Seal kit - Cartridge | Viton: 990-316-006 |

OPTION SELECTION EXAMPLE: RPIS8BWN

ADJUSTMENT RANGE

(B) SEAL MATERIAL

(N)

B 50 - 1500 psi (3,5 - 105 bar)

W 100 - 5000 psi (7 - 350 bar)

N Buna-N

E EPDM

V Viton

PERFORMANCE CURVES

