



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-18A
Series	4
Capacity	760 L/min.
Maximum Operating Pressure	350 bar
Factory Pressure Settings Established at	15 L/min.
Maximum Valve Leakage at 110 SUS (24 cSt)	80 cc/min.@70 bar
Response Time - Typical	10 ms
Adjustment - No. of CW Turns from Min. to Max. setting	5
Valve Hex Size	41,3 mm
Valve Installation Torque	474 - 508 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	1.18 kg.
Seal kit - Cartridge	Buna: 990-018-007
Seal kit - Cartridge	EPDM: 990-018-014
Seal kit - Cartridge	Polyurethane: 990-018-002
Seal kit - Cartridge	Viton: 990-018-006

OPTION SELECTION EXAMPLE: RPKCLAN

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
L	Standard Screw Adjustment	A	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting	N	Buna-N	Standard Material/Coating
C	Tamper Resistant - Factory Set	B	50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting	E	EPDM	/AP Stainless Steel, Passivated
W	Hex Wrench Adjustment	C	150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) Standard Setting	V	Viton	/LH Mild Steel, Zinc-Nickel
Y	manilla de tres agarres	D	25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting			
		E	25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting			
		N	60 - 800 psi (4 - 55 bar), 400 psi (28 bar) Standard Setting			
		Q	60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting			
		W	150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting			

PERFORMANCE CURVES

