



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-18A
Series	4
Capacity	760 L/min.
Maximum Operating Pressure	350 bar
Control Pilot Flow	0,25 - 0,33 L/min.
Main stage leakage at 110 SUS (24 cSt)	80 cc/min. @70 bar
Pilot Control Cavity	T-8A
Valve Hex Size	41,3 mm
Valve Installation Torque	474 - 508 Nm
Model Weight	0.59 kg.
Seal kit - Cartridge	Buna: 990-018-007
Seal kit - Cartridge	EPDM: 990-018-014
Seal kit - Cartridge	Polyurethane: 990-018-002
Seal kit - Cartridge	Viton: 990-018-006
Seal kit - Cartridge	Buna: 990-018-007
Seal kit - Cartridge	EPDM: 990-018-014
Seal kit - Cartridge	Polyurethane: 990-018-002
Seal kit - Cartridge	Viton: 990-018-006

OPTION SELECTION EXAMPLE: RPKC8WN

ADJUSTMENT RANGE

(W) SEAL MATERIAL

(N)

W 100 - 5000 psi (7 - 350 bar)	N Buna-N
D 25 - 3000 psi (1,7 - 210 bar)	E EPDM
	V Viton

PERFORMANCE CURVES

