



1

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|                      |                           |
|----------------------|---------------------------|
|                      | T-18A                     |
|                      | 4                         |
|                      | 760 L/min.                |
|                      | 350 bar                   |
| 110 SUS (24 cSt)     | 80 cc/min. @70 bar        |
|                      | 15 L/min.                 |
|                      | 2 ms                      |
| -                    | 5                         |
|                      | 41,3 mm                   |
|                      | 474 - 508 Nm              |
|                      | 4 mm                      |
|                      | 15 mm                     |
|                      | 9 - 10 Nm                 |
|                      | 1.17 kg.                  |
| Seal kit - Cartridge | Buna: 990-018-007         |
| Seal kit - Cartridge | Polyurethane: 990-018-002 |
| Seal kit - Cartridge | Viton: 990-018-006        |
| Seal kit - Cartridge | Buna: 990-018-007         |
| Seal kit - Cartridge | Polyurethane: 990-018-002 |
| Seal kit - Cartridge | Viton: 990-018-006        |

# OPTION SELECTION EXAMPLE: RPKELAN

|          | (L)      | (A)   | (N)      | MATERIAL/COATING          |
|----------|----------|---|----------|---------------------------|
| <b>L</b> | <b>A</b> | 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) | <b>N</b> | Standard Material/Coating |
|          |          | <b>Q</b>  | <b>V</b> | /AP                       |
|          |          | 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)     |          | /LH                       |

## TECHNICAL FEATURES

- 2
- 2
- 150
- 
- 2            1:1
- Sun            /

## PERFORMANCE CURVES

