



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-10A
	1
	95 L/min.
	350 bar
110 SUS (24 cSt)	30 cc/min. @70 bar
	Kick down point
	25 ms
-	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.14 kg.
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006

: •
• 0 1 0.75 in. (19 mm)

OPTION SELECTION EXAMPLE: RQEBLAN

	(L)	(A)	(N)	MATERIAL/COATING
L		A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	N	Standard Material/Coating
J			V	/AP
O		Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)		

TECHNICAL FEATURES

- 2
-
- 150
-
-
- 2 1:1
- /AP
- Sun /

PERFORMANCE CURVES

