



1 1 2 1 2

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-10A
	1
	95 L/min.
	350 bar
110 SUS (24 cSt)	30 cc/min.@70 bar
	Kick down point
	25 ms
-	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0,15 kg
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006

: •  
 • 0 1 0.75 in. (19 mm)

# OPTION SELECTION EXAMPLE: RQEBLANV

	(L)	(A)	(N)	MATERIAL/COATING
<b>L</b>	<b>A</b>	<b>N</b>	Standard Material/Coating	
<b>C</b>	<b>V</b>	/AP		
<b>C</b>	-			
	<b>A</b> 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) <b>B</b> 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) <b>C</b> 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) <b>D</b> 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) <b>E</b> 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) <b>N</b> 60 - 800 psi (4 - 55 bar), 400 psi (28 bar) <b>Q</b> 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) <b>W</b> 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)			

## TECHNICAL FEATURES

- 2
- 
- 150
- 
- 
- 2 1:1
- 
- /AP
- Sun /

## PERFORMANCE CURVES

