



CONFIGURATION

F Control	Hex Head Screw with Locknut
B Adjustment Range	50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting
N Seal Material	Buna-N
Material/Coating	

TECHNICAL DATA

NOTE:

cavidad	T-11A	DATA
Series	1	MAY
Capacity	60 L/min.	VARY
Maximum Operating Pressure	350 bar	BY
Control Pilot Flow	0,11 - 0,16 L/min.	
Factory Pressure Settings Established at	15 L/min.	
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min.@70 bar	
Response Time - Typical	10 ms	
Adjustment - No. of CW Turns from Min. to Max. setting	5	
Valve Hex Size	22,2 mm	
Valve Installation Torque	41 - 47 Nm	
Adjustment Screw Internal Hex Size	4 mm	
Locknut Hex Size	15 mm	
Locknut Torque	9 - 10 Nm	
Model Weight	0.14 kg.	
Seal kit - Cartridge	Buna: 990-011-007	
Seal kit - Cartridge	EPDM: 990-011-014	
Seal kit - Cartridge	Polyurethane: 990-011-002	
Seal kit - Cartridge	Viton: 990-011-006	
Seal kit - Cartridge	Buna: 990-011-007	
Seal kit - Cartridge	EPDM: 990-011-014	
Seal kit - Cartridge	Polyurethane: 990-011-002	CONFIGURATION. SEE
Seal kit - Cartridge	Viton: 990-011-006	CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: RSDCFBN

CONTROL	(F) ADJUSTMENT RANGE	(B) SEAL MATERIAL	(N) MATERIAL/COATING (/LH)
F Hex Head Screw with Locknut L Standard Screw Adjustment	B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting	N Buna-N E EPDM V Viton	/LH Mild Steel, Zinc-Nickel /AP Stainless Steel, Passivated Standard Material/Coating

PERFORMANCE CURVES

