



CONFIGURATION

L	
A	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)
N	
	Material/Coating

TECHNICAL DATA

NOTE:

	T-11A	DATA
	1	MAY
	60 L/min.	VARY
	350 bar	BY
	0,7 cc/min.	
	15 L/min.	
	10 ms	
	5	
	22,2 mm	
	41 - 47 Nm	
	15 mm	
	9 - 10 Nm	
	0.16 kg.	
Seal kit - Cartridge	Buna: 990-011-007	
Seal kit - Cartridge	Polyurethane: 990-011-002	
Seal kit - Cartridge	Viton: 990-011-006	

CONFIGURATION. SEE CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: RSDSLAN

	(L)	(A)	(N)	MATERIAL/COATING	(/LH)
L	-	A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	N	/LH -	
C	-	B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)	V	/AP	
		C 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar)			Standard Material/Coating
		N 60 - 800 psi (4 - 55 bar), 400 psi (28 bar)			
		Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)			
		W 100 - 4500 psi (7 - 315 bar), 1000 psi (70 bar)			

TECHNICAL FEATURES

- 3
- 3 1
- 150
- 3 1:1 3 5000 psi 350 bar
-
-
- 2
- Sun /

PERFORMANCE CURVES

