



### CONFIGURATION

<b>F</b> Control	Hex Head Screw with Locknut
<b>A</b> Adjustment Range	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting
<b>N</b> Seal Material	Buna-N
Material/Coating	

### TECHNICAL DATA

NOTE:

cavidad	T-2A	DATA
Series	2	MAY VARY
Capacity	120 L/min.	BY
Maximum Operating Pressure	350 bar	
Control Pilot Flow	0,16 - 0,25 L/min.	
Factory Pressure Settings Established at	15 L/min.	
Maximum Valve Leakage at 110 SUS (24 cSt)	50 cc/min.@70 bar	
Response Time - Typical	10 ms	
Adjustment - No. of CW Turns from Min. to Max. setting	5	
Valve Hex Size	28,6 mm	
Valve Installation Torque	61 - 68 Nm	
Adjustment Screw Internal Hex Size	4 mm	
Locknut Hex Size	15 mm	
Locknut Torque	9 - 10 Nm	
Model Weight	0.23 kg.	
Seal kit - Cartridge	Buna: 990-202-007	
Seal kit - Cartridge	EPDM: 990-202-014	
Seal kit - Cartridge	Polyurethane: 990-002-002	
Seal kit - Cartridge	Viton: 990-202-006	
Seal kit - Cartridge	Buna: 990-202-007	
Seal kit - Cartridge	EPDM: 990-202-014	
Seal kit - Cartridge	Polyurethane: 990-002-002	CONFIGURATION. SEE CONFIGURATION SECTION.
Seal kit - Cartridge	Viton: 990-202-006	CONFIGURATION SECTION.

## OPTION SELECTION EXAMPLE: RSFCFAN

CONTROL	(F)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING	(/LH)
<b>F</b> Hex Head Screw with Locknut		<b>A</b> 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting		<b>N</b> Buna-N		<b>/LH</b> Mild Steel, Zinc-Nickel	
<b>L</b> Standard Screw Adjustment				<b>E</b> EPDM		<b>/AP</b> Stainless Steel, Passivated	
				<b>V</b> Viton		Standard Material/Coating	

### PERFORMANCE CURVES

