



CONFIGURATION

F	
A	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)
N	
	Material/Coating

TECHNICAL DATA

NOTE:

	T-2A	DATA
	2	MAY
	120 L/min.	VARY
	350 bar	BY
110 SUS (24 cSt)	50 cc/min. @70 bar	
	15 L/min.	
	0,16 - 0,25 L/min.	
	10 ms	
-	5	
	28,6 mm	
	61 - 68 Nm	
	4 mm	
	15 mm	
	9 - 10 Nm	
	0.23 kg.	
Seal kit - Cartridge	Buna: 990-202-007	
Seal kit - Cartridge	EPDM: 990-202-014	
Seal kit - Cartridge	Polyurethane: 990-002-002	
Seal kit - Cartridge	Viton: 990-202-006	
Seal kit - Cartridge	Buna: 990-202-007	
Seal kit - Cartridge	EPDM: 990-202-014	
Seal kit - Cartridge	Polyurethane: 990-002-002	CONFIGURATION. SEE
Seal kit - Cartridge	Viton: 990-202-006	CONFIGURATION SECTION.

: • O 1 0.75 in. (19 mm)

OPTION SELECTION EXAMPLE: RSFCFAN

	(F)	(A)	(N)	MATERIAL/COATING	(/LH)
F	A	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	N	/LH -	/AP
			E EPDM V		Standard Material/Coating

TECHNICAL FEATURES

- 3
- 3 1
- 150
- 3 1:1 3 5000 psi 350 bar
-
- W Y
- EPDM
- Sun /

PERFORMANCE CURVES

