



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-2A
	2
	120 L/min.
	350 bar
	0,7 cc/min.
	15 L/min.
	10 ms
	5
	28,6 mm
	61 - 68 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0,25 kg
Seal kit - Cartridge	Buna: 990-402-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-402-006
Seal kit - Cartridge	Buna: 990-402-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-402-006

OPTION SELECTION EXAMPLE: RSFSLANN

	(L)	(A)	(N)	MATERIAL/COATING
L	A	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	N	Standard Material/Coating
		N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar)	V	/AP
		Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)		

TECHNICAL FEATURES

- 3
- 3 1
- 150
- 3 1:1 3 5000 psi 350 bar
-
-
- 2
- Sun /

PERFORMANCE CURVES

