



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-17A
	3
	240 L/min.
	350 bar
110 SUS (24 cSt)	65 cc/min.@70 bar
	15 L/min.
	0,25 - 0,33 L/min.
	10 ms
-	5
	31,8 mm
	203 - 217 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.62 kg.
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

OPTION SELECTION EXAMPLE: RSHCLAN

	(L)	(A)	(N)	MATERIAL/COATING
L	-	A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	N	Standard Material/Coating
C	-		E EPDM	/AP
K		B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)	V	/LH -
Y		C 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar)		
		D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar)		
		E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)		
		N 60 - 800 psi (4 - 55 bar), 400 psi (28 bar)		
		W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)		

TECHNICAL FEATURES

- 3
- 3 1
- 150
- 3 1:1 3 5000 psi 350 bar
-
- W Y
- Sun /

PERFORMANCE CURVES

