



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-17A
Series	3
Capacity	240 L/min.
Maximum Operating Pressure	140 bar
Pilot Ratio	20:1
Factory Pressure Settings Established at	15 L/min.
Maximum Air Pressure	10,5 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	65 cc/min.
Response Time - Typical	10 ms
Valve Hex Size	31,8 mm
Valve Installation Torque	203 - 217 Nm
Model Weight	0.60 kg.
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

OPTION SELECTION EXAMPLE: RSHEBBN

CONTROL

(B) ADJUSTMENT RANGE

(B) SEAL MATERIAL

(N)

B External 4-SAE Port

B 50 - 1500 psi (3,5 - 105 bar)

N Buna-N

V Viton

PERFORMANCE CURVES

