



PORT 3  
DRAIN

PORT 2  
SEQUENCE

PORT 1  
INLET

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-17A
Series	3
Capacity	240 L/min.
Maximum Operating Pressure	350 bar
Control Pilot Flow	0,25 - 0,33 L/min.
Main stage leakage at reseal	0,7 cc/min.
Pilot Control Cavity	T-8A
Pilot Control Valve Hex Size	22,2 mm
Pilot Control Valve Installation Torque	27 - 33 Nm
Response Time - Typical	2 ms
Valve Hex Size	31,8 mm
Valve Installation Torque	203 - 217 Nm
Model Weight	0.50 kg.
Seal kit - Cartridge	Buna: 990-217-007
Seal kit - Cartridge	Polyurethane: 990-217-002
Seal kit - Cartridge	Viton: 990-217-006

# OPTION SELECTION EXAMPLE: RSHS8WN

MINIMUM CONTROL PRESSURE

(W) SEAL MATERIAL

(N)

W 100 psi (7 bar)  
 B 50 psi (3,5 bar)

N Buna-N  
 V Viton

## PERFORMANCE CURVES

