



1

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------|---------------------------|
| | T-19A |
| | 4 |
| | 480 L/min. |
| | 140 bar |
| | 20:1 |
| 110 SUS (24 cSt) | 80 cc/min. |
| | 15 L/min. |
| | 10,5 bar |
| | 10 ms |
| | 41,3 mm |
| | 474 - 508 Nm |
| | 1.41 kg. |
| Seal kit - Cartridge | Buna: 990-019-007 |
| Seal kit - Cartridge | Polyurethane: 990-019-002 |
| Seal kit - Cartridge | Viton: 990-019-006 |
| Seal kit - Cartridge | Buna: 990-019-007 |
| Seal kit - Cartridge | Polyurethane: 990-019-002 |
| Seal kit - Cartridge | Viton: 990-019-006 |

OPTION SELECTION EXAMPLE: RSJEBBN

(B)

(B)

(N)

B 4-SAE

B 50 - 1500 psi (3,5 - 105 bar)

N

V

TECHNICAL FEATURES

- 3
- 3 1
- 150 psi 10,5 bar
- 3 1000 psi 70 bar
- 20:1
- Sun /

PERFORMANCE CURVES

